

GOLD COAST GENERATORS
 Unit 14, 225A Brisbane Road
 Labrador, QLD 4216
 Tel: (07) 5529 0351 Fax: (07) 5529 0416
 Email: Info@goldcoastgenerators.com.au

GS6000



Single Cylinder
4 Stroke
Vertical Shaft
Air Cooled
OHV
Petrol Engine

RATING NOTES

kVA	6.0kVA	Volts	240V
Rated Current (A)	24A	Frequency	50 hZ
Rated Speed (RPM)	3600 RPM	kW (rated/max) Output	5500 / 6000 watts

TECHNICAL INFORMATION

DC Output	12V-8.3A	Phase	Single
Oil Capacity	1.1ltr	Fuel tank capacity	22 ltr
Continuous Run time @ rated output	6 hrs	Noise Level – dB (A)/7m	65-71 dB
Start Method	Electric Start	Fuel Type	Unleaded Petrol
Lube Oil	SAE 10W 30	Displacement	389 cc
Compression Ratio	8.5:1	Max Pwer (kW)/(RPM)	7.7kW / 3600 RPM
Ignition System	Electronic	Spark Plug	BPR6ES

DIMENSIONAL & WEIGHT INFORMATION

Length	802mm	Width	495mm
Height	424mm	Dry Weight	95kg

2 year warranty for domestic use and 1 year for commercial use

Spec details valid as of Dec '08 & subject to change without notice